

1. 3M Outdoor IP Camera

Feature:

- Max resolution can reach 1.3M(1280×960), HD 720P output, real-time image
- Low illumination, 0.01Lux @ (F1.2, AGC ON), 0 LUX with IR
- Support IR-CUT filter switch to achieve day and night monitoring
- H.264 main profile compression, achieve low bit-rate, high definition image quality
- Support dual stream
- Support Standard Onvif protocol
- Support mobile monitor (iPhone, Windows Mobile, BlackBerry, Symbian, Android)
- Support electronic shutter, adjust for different surveillance environment
- Provide web, CMS, and SDK for development
- Support connection with HVR/NVR/NVD
- Accord with IP66 waterproof design



Specification:

Model	C1-1366
Image Sensor	1/3" AR0130 super illumination CMOS sensor
Effective Pixel	1280 x 960
Min illumination	Color: 0.01Lux @ (F1.2, AGC ON), 0 LUX with IR B/W: 0.001Lux @ (F1.2, AGC ON), 0 LUX with IR
Electronic shutter	1/50(1/60)s - 1/100,000 s
Lens	4mm fix Iris
Day & Night	Support IR-CUT
Video compression	H.264 Main Profile, JPEG capture
Video Bite Rate	100Kbps~6Mbps
Resolution	Main streams: 1280 × 960, 1280 x 720 ; Sub-Streams: 704 x 480
Frame Rate	50Hz: 25fps (1280*960); 60Hz: 30fps (1280*960);
Image settings	Saturation, Brightness, Contrast adjustable through Client software or web server
Intelligent Alarm	Motion detect, video loss, network disconnection, IP address conflict, storage full, storage error
Protocol	TCP/IP, HTTP, DHCP, DNS, DDNS, PPPoE, SMTP, NTP, Onvif (HTTPS, SIP, 802.1x, IPv6 optional)
Basic	Anti-flicker, dual stream, heartbeat, password protection
Communication Interface	RJ45 10M/100M, self-adaptive Ethernet interface
Operating condition	-10℃ ~ 60℃ , humidity 90% less (non-condensing)
Power supply	DC12V/1A
POE power supply	Optional
Power consumption	8.5W MAX;
Protection Range	IP66
IR distance	25 M
Dimension(mm)	77 x 80 x 140 mm
Weight	450g