

4-AXIS IR LED DAY & NIGHT VANDAL DOME CAMERA

FEATURE :

- Camera with 1/3" SONY Spuer HAD CCD II sensor
- Signal system : PAL or NTSC system.
- Vandal dome is designed with 4-Axis for angle view flexibility.
- Polycarbonate shell withstand the impact of 380Kgf
- Built in Varifocal Auto Iris Lens for better clear image.
- OSD function supported.(Option)
- DC12V/AC24V switches automatically power supply.
- Option:Heater



AC24V/DC12V



4 AXIS Angle Adjustment

SPECIFICATION :

Model	CVR-63A7ASIR	CVR-62A0
Image CCD Sensor	1/3" SONY Super HAD CCD II	
Effective Pixels	NTSC: 1020x508 PAL: 1020x596	
H-Resolution	700TV Lines	
Sensitivity	0.08Lux@F1.2	
Video Output	1.0Vpp Composite , 75 Ohms	
S/N Ratio	More Than 52dB(AGC/Off)	
Electronic Shutter	1/50(60)sec ~ 1/110,000 (1/100,000)sec	
Wide Dynamic Range	D-WDR	
BackLight	HLC/BLC/MASK/Off	
2D-DNR	2D	
White Balance	ATW1/ATW2/AWC-SET/ANTI CRL/Manual	
Motion Detection	48x15 Zones	
Privacy Masking	8 Zones	
OSD	Yes/9 Languages	
LENS type	2.8~12mm Auto IRIS F1.4	4mm,6mm,8mm,12mm/F2.0 Board Lens
IR LED	24 pcs IR LED	
Outdoor Protected	IP67	
Power Supply	DC12V or DC12V/AC24V dual voltage(Optional)	
Operation Temp.	-10℃ ~ 50℃ , Heater Function:-25℃ ~ 50℃	
Operation Humidity	RH80% or less	

Product Selection Guide

CVR-62A0	700TVL OSD with IR Vandal Dome	CVR-63A7ASIR	2.8~12mm 700TVL OSD with IR Vandal Dome
----------	--------------------------------	--------------	---