

4CH / 8CH HD SDI DVR

Feature:

- Special for HD-SDI cameras;
- Up to 8 channels of HD-SDI cameras can be connected;
- Simultaneous HDMI and VGA outputs;
- All channels simultaneous playback; Simultaneous playback resolution is up to 1920*1080P@30fps;
- Up to 8 channels audio inputs;
- Smart search for the event triggered record files;
- HDD quota management; different capacities can be assigned to different channels.
- 1 self-adaptive 10M/100M/1000M Network interface;
- Support iPhone or Android Mobile phone surveillance.
- TCP/IP, PPPoE, DHCP, DNS, DDNS, NTP, SADP, SMTP, SNMP, NFS, iSCSI and UPnP™ protocols are supported;



Specification:

Model		HID0402L	HID0802L
Video/Audio Input	Video Compression	H.264	
	HD-SDI video input	4-ch HD-SDI interface; (800mVp-p, 75Ω)	8-ch HD-SDI interface; (800mVp-p, 75Ω)
	Supported SDI Camera	1080I/60, 1080I/50, 1080P/30, 1080P/25, 720P/60, 720P/50, 720P/30, 720P/25	
	Audio Compression	G.711u	
	Audio Input	4-ch RCA (2.0 Vp-p, 1 kΩ)	8-ch RCA (2.0 Vp-p, 1 kΩ)
	2 Way Audio In	1-ch, RCA (2.0 Vp-p, 1 kΩ), (using the 1st channel of audio input)	
Video/Audio Output	VGA Output	1280 × 720 / 60 Hz, 1024 × 768 / 60 Hz	
	HDMI Output	1920 × 1080 / 60 Hz (1080P), 1280 × 1024 / 60 Hz	
	Encoding resolution	Main stream: 1920 × 1080 (1080P) / 1280 × 720 / VGA / 4CIF / CIF	
		Sub-stream: 4CIF(non-real-time) / CIF / QCIF / QVGA	
	Recording resolution	1080P/720P/VGA/4CIF/CIF	
	Frame Rate	Main stream: 1/16 fps ~ Real time frame rate	
	Video Bit Rate	32 Kbps-16384 Kbps user defined (Max. 16384 Kbps)	
	Stream Type:	Video / Video & Audio	
	Audio Output:	1-ch RCA(Linear, 1kΩ)	
	Audio Bit Rate	64kbps	
	Dual Stream	Support	
	Playback resolution	1920 × 1080 (1080P) / 1280 × 720 / VGA / 4CIF / CIF	
	Synchronous Playback	2-ch, 1080P / 4-ch, 4CIF	2-ch, 1080P / 8-ch, 4CIF
Hard Disk Driver	Interface Type	2 SATA Interfaces	
	Capacity	Up to 4TB capacity for each disk	
External Interface	Network Interface	1 RJ45 10M/100M/1000M adaptive Ethernet Interface	
	USB Interface	2 USB 2.0 Interfaces	
	Serial Interface	1 RS-485 interface	
Alarm Interface	In /Out	4 In / 1 Out	4 In / 1 Out
General	Power Supply	12 VDC	
	Consumption	≤ 15 W	≤ 20 W
	Working Temperature	-10 °C ~ +55 °C	
	Working Humidity	10% ~ 90%	
	Chassis	19-inch rack-mounted 1U chassis	
	Dimensions	445 × 290 × 45 mm (W × D × H)	
	Weight	≤ 4 kg (without hard disk or DVD-R/W)	