

16ch 960H DVR

Feature:

- H.264 video compression
- 16-ch Video Input
- WD1 resolution real time recording
- HDMI/VGA output at 1920×1080P resolution
- Gigabit network interface
- Up to 16-ch synchronous playback
- HDD quota and group management



Specification:

Model		SD-1604WH
Video / Audio Input	Video Compression:	H.264
	Analog Video Input:	16-ch
	PAL/NTSC Adaptive:	Support
	Video Input Interface:	BNC (1.0 Vp-p, 75Ω)
	Audio Compression:	G.711
	Audio Input:	4-ch
	Audio Input Interface:	RCA (2.0 Vp-p, 1 kΩ)
	Two-way Audio:	1-ch RCA(2.0Vp-p, 1kΩ)
Video / Audio Output	VGA Output:	1-ch, resolution: 1920×1080P/60Hz, 1280×1024/60Hz, 1280×720/60Hz, 1024×768/60Hz
	CVBS Output:	2-ch (1 Main Video Out+1 Spot Video Out), BNC (1.0 Vp-p, 75 Ω), resolution: PAL: 704×576, NTSC: 704×480
	HDMI Output:	1-ch, resolution: 1920×1080P /60 Hz, 1280×1024 /60 Hz, 1280×720 /60 Hz, 1024×768 /60 Hz.
	Recording resolution:	WD1/ 4CIF / 2CIF / CIF / QCIF
	Frame Rate:	25 fps (P) / 30 fps (N)
	Video Bit Rate:	32 Kbps ~ 3072 Kbps, or user defined (Max. 3072 Kbps)
	Stream Type:	Channel 1-4: Video, Video & Audio; Other channels: Video
	Audio Output:	2-ch RCA(Linear electrical level, 600Ω)
	Audio Bit Rate:	64kbps
	Dual Stream:	Support
	Synchronous Playback:	16-ch
Hard Disk Driver	Interface Type:	4 SATA interfaces for 2 HDDs + 1 DVD-R/W (default), or 4HDDs
	Capacity:	Up to 4TB capacity for each disk
	e-SATA Interface:	1 eSATA interface
External Interface	Network Interface:	1 RJ45 10M/100M/1000M adaptive Ethernet Interface
	USB Interface:	3 USB2.0 interfaces
	Serial Interface:	1RS-485 interface, 1 RS-232 interface, 1 RS-485 keyboard interface
	Alarm Input:	16-ch
	Alarm Output:	4-ch
General	Power Supply:	100 ~ 240 VAC, 5A, 50~60Hz
	Consumption:	≤ 35W (without hard disk or DVD-R/W)
	Working Temperature:	-10 °C ~ + 55 °C
	Working Humidity:	10% ~ 90%
	Chassis:	19-inch rack-mounted 1.5 U chassis
	Dimensions:	445(W) × 390(D) × 70(H) mm
	Weight:	≤ 5kg (without hard disk or DVD-R/W)