

# VARI-FOCAL

## DOME CCD CAMERA



### Product Feature

- ▶ Camera with 1/3" SONY Super HAD CCD Sensor
- ▶ Signal system: PAL or NTSC system
- ▶ Built-in Auto Iris Lens for better/clear image
- ▶ Using 3.8~9.5mm Varifocal Lens which can make any adjustment according to any different environment request
- ▶ Built-in Auto electronic shutter
- ▶ Auto White Balance control

### Specification:

Model	CDC-3310	CDC-4312
Image CCD Sensor	COLOR 1/3" SONY Super HAD CCD	
Picture Elements	NTSC: 542 x 492 PAL : 542 x 582	NTSC: 811 x 508 PAL: 795 x 596
H-Resolution	420 TVL	530 TVL
Min. Illumination	0.1Lux @ F1.2	0.5 Lux @ F1.2
Scanning system	NTSC: 525 lines, PAL: 625 lines. 2:1 interlace	
Video output	Composite: 1.0 Vp-p, 75Ohms	
S/N Ratio	More than 48dB	
Electronic Shutter	NTSC: 1/60~1/100,000. ; PAL: 1/50~1/110,000.	
Lens type	3.8mm~9.5mm Varifocal Auto Iris Lens, F1.2	
Back light control	AUTO control	
White Balance	AUTO control	
Power Supply	DC12V / 300mA	
Power consumption	Max. 3.2W	
Operation Humidity	RH85% or less	
Operating Temp.	-10°C ~ +50°C	



# MINI DOME

## COLOR CAMERA

### Product Feature

- ▶ Camera with 1/3" SONY Super HAD CCD Sensor
- ▶ Signal system: PAL or NTSC system
- ▶ Built-in Auto electronic shutter
- ▶ Auto White Balance control
- ▶ Built-in 3.6mm Lens, Option 6/8/12mm Lens

### Specification:

Model	CDC-1305	CDC-2305
Image CCD Sensor	COLOR 1/3" SONY Super HAD CCD	
Picture Elements	NTSC: 542 x 492 PAL : 542 x 582	NTSC: 811 x 508 PAL: 795 x 596
H-Resolution	420 TVL	530 TVL
Min. Illumination	0.3 Lux @ F1.2	0.5 Lux @ F1.2
Scanning system	NTSC: 525 lines, PAL: 625 lines. 2:1 interlace	
Video output	Composite: 1.0 Vp-p, 75Ohms	
S/N Ratio	More than 48dB	
Electronic Shutter	NTSC: 1/60~1/100,000. ; PAL: 1/50~1/110,000.	
Lens type	Standard:3.6mm Lens/ Option: 6mm;8mm Lens	
Back light control	AUTO control	
White Balance	AUTO control	
Power Supply	DC12V/300mA	
Power consumption	Max. 3.2W	
Operation Humidity	RH85% or less	
Operating Temp.	-10°C ~ +50°C	

## PRODUCT SELECTION GUIDE

