INDOOR IR

DOME COLOR CAMERA

Product Feature

- Camera with 1/3" SONY Super HAD CCD Sensor
- Signal system: PAL or NTSC system
- IR Camera built-in 12pcs IR LED
- Packing camera, Lens, IR LED all in one
- Built-in Auto electronic shutter
- Auto White Balance control
- Built-in 6.0mm Lens, Option 4.3/8/12mm Lens

Specification:

Model	CIC-1302	CIC-2302
Image CCD Sensor	COLOR 1/3" SONY Super HAD CCD	
Picture Elements	NTSC: 542 x 492 PAL : 542 x 582	NTSC: 811 x 508 PAL: 795 x 596
H-Resolution	420 TVL	530 TVL
Min. Illumination	0.1Lux @ F1.2	0.5 Lux @ F1.2
Scanning system	NTSC: 525 lines, PAL: 625 lines. 2:1 interlace	
Video output	Composite: 1.0 Vp-p, 75Ohms	
S/N Ratio	More than 48dB	
Electronic Shutter	NTSC: 1/60~1/100,000. ; PAL: 1/50~1/110,000.	
Lens type	Standard: 3.6mm Lens/ Option: 6mm;8mm Lens	
Back light control	AUTO control	
White Balance	AUTO control	
Power Supply	DC12V / 300mA	
Power consumption	Max. 3.2W	
Operation Humidity	RH85% or less	
Operating Temp.	-10℃ ~ +50℃	

SMOKE DETECTOR CAMERA

DOME COLOR CAMERA

Product Feature

- Camera with 1/3" SONY Super HAD CCD Sensor
- Signal system: PAL or NTSC system
- Built-in Auto electronic shutter
- Auto White Balance control
- Built-in 3.6mm Lens, Option 6/8/12mm Lens

Specification:

Model	CSC-1302	CSC-2302
Image CCD Sensor	COLOR 1/3" SONY Super HAD CCD	
Picture Elements	NTSC: 542 x 492 PAL : 542 x 582	NTSC: 811 x 508 PAL: 795 x 596
H-Resolution	420 TVL	530 TVL
Min. Illumination	0.3Lux @ F1.2	0.5 Lux @ F1.2
Scanning system	NTSC: 525 lines, PAL: 625 lines. 2:1 interlace	
Video output	Composite: 1.0 Vp-p, 75Ohms	
S/N Ratio	More than 48dB	
Electronic Shutter	NTSC: 1/60~1/100,000. ; PAL: 1/50~1/110,000.	
Lens type	Standard: 3.6mm Lens/ Option: 6mm;8mm Lens	
Back light control	AUTO control	
White Balance	AUTO control	
Power Supply	DC12V / 300mA	
Power consumption	Max. 3.2W	
Operation Humidity	RH85% or less	
Operating Temp.	-10℃ ~ +50℃	

PRODUCT SELECTION GUIDE

CDC-□□□□ □□

- **N:** NTSC system
- **P:** PAL system
- **A:** DC12V